

Model	<i>FS-60B</i>
Rated Power	70W
Input Voltage/Current	AC100-240V 50/60Hz
CCT	2700K-6500K
CRI	Average 96
TLCI	Average 97
Dimming	0-100% continuous
Control	On-board , 2.4G, Bluetooth, NANLINK APP
Special Effects	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding.
Product Size	Light Fixture(without protective cap): 247 × 134 × 87mm / 9.72 × 5.28 × 3.43"
Product Weight	Light Fixture : 0.85kg / 1.87lb
Master Carton Size	665 × 385 × 380mm / 26.2" × 15.2" × 14.9"
Packing Quantity	8
Certifications	ROHS, CE, UKCA, PSE, NCC, KCC, FCC-ID

Model	FS-60B		
Light Only			
Distance	1M	2M	3M
2700K	2467 lux / 229 fc	636 lux / 59 fc	296 lux / 27 fc
3200K	2630 lux / 244 fc	679 lux / 63 fc	315 lux / 29 fc
5600K	2799 lux / 260 fc	723 lux / 67 fc	339 lux / 31 fc
6500K	2791 lux / 259 fc	720 lux / 67 fc	339 lux / 31 fc
With Reflector			
Distance	1M	2M	3M
2700K	11350 lux / 1054 fc	2536 lux / 236 fc	1096 lux / 102 fc
3200K	12370 lux / 1149 fc	2720 lux / 253 fc	1175 lux / 109 fc
5600K	13360 lux / 1241 fc	2959 lux / 275 fc	1272 lux / 118 fc
6500K	13250 lux / 1231 fc	2925 lux / 272 fc	1252 lux / 116 fc
With FL-11 Spot			
Distance	1M	2M	3M
2700K	27890 lux / 2591 fc	6610 lux / 614 fc	2906 lux / 270 fc
3200K	30260 lux / 2811 fc	7092 lux / 659 fc	3080 lux / 286 fc
5600K	32510 lux / 3020 fc	7635 lux / 709 fc	3318 lux / 308 fc
6500K	32380 lux / 3008 fc	7604 lux / 706 fc	3308 lux / 307 fc
With FL-11 Flood			

Distance	1M	2M	3M
2700K	6843 lux / 636 fc	1690 lux / 157 fc	758 lux / 70 fc
3200K	7645 lux / 710 fc	1805 lux / 168 fc	810 lux / 75 fc
5600K	8223 lux / 764 fc	1932 lux / 179 fc	871 lux / 81 fc
6500K	8134 lux / 756 fc	1920 lux / 178 fc	864 lux / 80 fc

With PJ-FMM-19

Distance	1M	2M	3M
2700K	39150 lux / 3637 fc	7258 lux / 674 fc	2942 lux / 273 fc
3200K	41450 lux / 3851 fc	7718 lux / 717 fc	3191 lux / 296 fc
5600K	44320 lux / 4117 fc	8292 lux / 770 fc	3360 lux / 312 fc
6500K	44160 lux / 4102 fc	8212 lux / 763 fc	3356 lux / 312 fc

With PJ-FMM-36

Distance	1M	2M	3M
2700K	15430 lux / 1433 fc	2926 lux / 272 fc	1219 lux / 113 fc
3200K	16470 lux / 1530 fc	3134 lux / 291 fc	1303 lux / 121 fc
5600K	17730 lux / 1647 fc	3451 lux / 321 fc	1425 lux / 132 fc
6500K	17680 lux / 1642 fc	3428 lux / 318 fc	1413 lux / 131 fc