

Technical Data

Model	<i>PavoSlim 240B</i>	<i>PavoSlim 240C</i>
Rated Power	260W	
Input Voltage/Current	AC 100-240V 50/60HZ DC 48V/5.6A DC(Battery)14.4-26V	
CCT	2700K-6500K	2700K-7500K(G/M ± 150)
CRI	Average 95	Average 96
TLCI	Average 97	
TM-30 Rf	Average 95	Average 94
TM-30 Rg	Average 102	Average 100
SSI [3200K]	83	83
SSI [5600K]	73	74
Dimming	0-100%	
LED Type	WW	RGBWW
Control	On-board, Remote Controller, DMX/RDM, NANLINK APP	On-board, Remote Controller, DMX/RDM, LumenRadio CRMX, NANLINK APP
Special Effects	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding	HUE Loop, CCT Loop, INT Loop, Flash, Pulse, Storm, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding
Product Size	Light Fixture: Unfolded: 608.7 × 602.1 × 28.6mm / 23.96 × 23.70 × 1.13" Folded: 318.4 × 602.1 × 38.2mm / 12.54 × 23.70 × 1.50" Control Unit: 152.6 × 111.5 × 283mm / 6.01 × 4.39 × 11.14"	
Product Weight	Light Fixture: 3.44kg / 7.58lb Control Unit: 2.65kg / 5.84lb	Light Fixture: 3.65kg / 8.05lb Control Unit: 2.76kg / 6.08lb
Certifications	CE, UKCA, RoHS, PSE, KCC, BIS, FCC-ID, SAA+C-Tick, ETL+cETL, NCC	

Illumination (lux / fc)

PavoSlim 240C

Light Only

Distance	0.5M	1M	3M
2700K	52270 lux / 4856 fc	20690 lux / 1922 fc	2868 lux / 296 fc
3200K	57230 lux / 5317 fc	22770 lux / 2115 fc	3130 lux / 291 fc
4300K	62000 lux / 5760 fc	24280 lux / 2256 fc	3343 lux / 311 fc
5600K	63650 lux / 5913 fc	24970 lux / 2320 fc	3441 lux / 320 fc
6500K	63120 lux / 5864 fc	24930 lux / 2316 fc	3432 lux / 319 fc
R	27270 lux / 2533 fc	10390 lux / 965 fc	1364 lux / 127 fc
G	48710 lux / 4525 fc	16770 lux / 1558 fc	2145 lux / 199 fc
B	9170 lux / 852 fc	2060 lux / 191 fc	260 lux / 24 fc

With Softbox and Lite Diffuser

Distance	0.5M	1M	3M
2700K	29750 lux / 2764 fc	9960 lux / 925 fc	1275 lux / 118 fc
3200K	32940 lux / 3060 fc	10900 lux / 1013 fc	1398 lux / 130 fc
4300K	35250 lux / 3275 fc	11640 lux / 1081 fc	1499 lux / 139 fc
5600K	36140 lux / 3357 fc	12010 lux / 1116 fc	1533 lux / 142 fc
6500K	35900 lux / 3335 fc	11870 lux / 1103 fc	1527 lux / 142 fc
R	16260 lux / 1511 fc	5430 lux / 504 fc	696 lux / 65 fc
G	28330 lux / 2632 fc	9080 lux / 844 fc	1154 lux / 107 fc
B	5440 lux / 505 fc	1130 lux / 105 fc	143 lux / 13 fc

With Softbox and Standard Diffuser

Distance	0.5M	1M	3M
2700K	16180 lux / 1503 fc	4575 lux / 425 fc	565 lux / 52 fc
3200K	17910 lux / 1664 fc	5011 lux / 466 fc	619 lux / 58 fc
4300K	19140 lux / 1778 fc	5366 lux / 499 fc	664 lux / 62 fc
5600K	19530 lux / 1814 fc	5517 lux / 513 fc	681 lux / 63 fc
6500K	19350 lux / 1798 fc	5483 lux / 509 fc	675 lux / 63 fc
R	9230 lux / 857 fc	2571 lux / 239 fc	327 lux / 30 fc
G	15470 lux / 1437 fc	4334 lux / 403 fc	535 lux / 50 fc
B	2040 lux / 190 fc	570 lux / 53 fc	70 lux / 7 fc