

Technical Data

Model	PavoTube II 15X/XR	PavoTube II 30X/XR	PavoTube II 60X/XR
Rated Power	35W	70W	106W
Input Voltage/Current	DC 15V/2A Max AC 100-240V 50/60Hz	DC 15V/4A Max AC 100-240V 50/60Hz	DC 15V/6.5A Max AC 100-240V 50/60Hz
CRI	Average 97		
TLCI	Average 98		
CCT	2700K-12000K (G/M)		
Dimming	0-100%		
Control	On-board, Remote Controller, NANLINK APP, DMX/RDM, *LumenRadio CRMX (*Only available for PavoTube II 15XR/30XR/60XR)		
Effect	HUE Loop, CCT Loop, INT Loop, Flash, Pulse, Storm, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding		
Pixel Effect	HUE Loop, CCT Loop, INT Loop, Multi-color, Fade, Scroll, Rainbow, *Process, *Fire, *Driving (*Only APP Control)		
Product Size	Light Fixture: φ43 × 600mm / φ1.69 × 23.6"	Light Fixture: φ43 × 1145mm / φ1.69 × 45.07"	Light Fixture: φ43 × 2220mm / φ1.69 × 87.4"
Product Weight	Light Fixture: 0.82kg / 1.81lb 15V/2A Power Adapter: 0.2kg / 0.44lb Power Cable 3M: 0.05kg / 0.11lb	Light Fixture: 1.58kg / 3.48lb 15V/4A Power Adapter: 0.27kg / 0.60lb Power Cable 3M: 0.05kg / 0.11lb	Light Fixture: 2.9kg / 6.39lb 15V/6.5A Power Adapter: 0.55kg / 1.21lb Power Cable 3M: 0.05kg / 0.11lb
Certifications	RoHS, FCC, CE, UKCA, PSE, NCC, KUKAS		RoHS, CE, UKCA, PSE, KUKAS

Illumination (lux / fc)

PavoTube II 15X/XR

Distance	1M	2M	3M
2700K	343 lux / 32 fc	86 lux / 8 fc	38 lux / 4 fc
3200K	350 lux / 33 fc	87 lux / 8 fc	39 lux / 4 fc
5600K	377 lux / 35 fc	94 lux / 9 fc	42 lux / 4 fc
6500K	386 lux / 36 fc	97 lux / 9 fc	43 lux / 4 fc

PavoTube II 15X/XR

Distance	1M	2M	3M
R	150 lux / 14 fc	39 lux / 4 fc	17 lux / 2 fc
G	308 lux / 29 fc	77 lux / 7 fc	34 lux / 3 fc
B	63 lux / 6 fc	15 lux / 1 fc	7 lux / 1 fc

PavoTube II 30X/XR

Distance	1M	2M	3M
2700K	686 lux / 64 fc	174 lux / 16 fc	78 lux / 7 fc
3200K	688 lux / 64 fc	175 lux / 16 fc	78 lux / 7 fc
5600K	746 lux / 69 fc	189 lux / 18 fc	84 lux / 8 fc
6500K	770 lux / 72 fc	194 lux / 18 fc	87 lux / 8 fc
R	272 lux / 25 fc	69 lux / 6 fc	30 lux / 3 fc
G	586 lux / 54 fc	144 lux / 13 fc	64 lux / 6 fc
B	123 lux / 11 fc	31 lux / 3 fc	14 lux / 1 fc

PavoTube II 60X/XR

Distance	1M	2M	3M
2700K	900 lux / 84 fc	336 lux / 31 fc	180 lux / 17 fc
3200K	928 lux / 86 fc	345 lux / 32 fc	184 lux / 17 fc
5600K	991 lux / 92 fc	369 lux / 34 fc	194 lux / 18 fc
6500K	1024 lux / 95 fc	380 lux / 35 fc	201 lux / 19 fc
R	332 lux / 31 fc	131 lux / 12 fc	68 lux / 6 fc
G	783 lux / 73 fc	295 lux / 27 fc	153 lux / 14 fc
B	143 lux / 13 fc	55 lux / 5 fc	28 lux / 3 fc