

|                                                |                                                 |
|------------------------------------------------|-------------------------------------------------|
| Angle of view (horizontal, vertical, diagonal) | 20° - 6° 50',<br>14° - 4° 35',<br>24° - 8° 15', |
| Optical structure (lenses/groups)              | 23/18                                           |
| Special lenses                                 | 1 x Fluorite<br>4 x UD<br>1 x GMo aspherical,   |
| Number of aperture blades                      | 9                                               |
| Smallest aperture                              | 22                                              |
| Close focusing distance (approx. m)            | 1.8 m (constant)                                |
| Largest magnification (x)                      | 0.06 (at 100mm)<br>0.16 (at 300mm)              |
| Steering ring                                  | Yes                                             |
| Optical Image Stabilizer (OIS <sup>1)</sup>    | 5.5                                             |
| Image stabilization IBIS x OIS                 | 6                                               |
| AF motor                                       | Dual Nano USM                                   |
| Remuneration                                   | ASC, Super Spectra                              |
| fluorine                                       | front lens                                      |

## Accessories

|                             |                                   |
|-----------------------------|-----------------------------------|
| lens cap                    | E-112                             |
| Lens hood                   | ET-124                            |
| Lens case/bag               | Lens case LS100-300               |
| Lens rear cap               | RF lens cap                       |
| compatibility with extender | Yes, compatible with RF extenders |

## Specifications with 1.4x extender

|                       |           |
|-----------------------|-----------|
| Focal length          | 140-420mm |
| Maximum aperture      | 4         |
| Maximum magnification | 0.22      |
| AF possible           | Yes       |
| Image stabilizer      | Yes       |

## Specifications with 2x extender

|                       |           |
|-----------------------|-----------|
| Focal length          | 200-600mm |
| Maximum aperture      | 5.6       |
| Maximum magnification | 0.31      |
| AF possible           | Yes       |
| Image stabilizer      | Yes       |

## General Information

|                                |                        |
|--------------------------------|------------------------|
| Dust/splash water protection   | Yes,                   |
| Exterior coating               | Heat-resistant coating |
| Filter diameter (approx. mm)   | 112                    |
| Diameter x Length (approx. mm) | 128 x 323,4            |
| Weight (approx. g)             | 2,590                  |