

Image size	Full format
Angle of view (horizontal, vertical, diagonal)	02°35', 01°40', 03°05'
Optical structure (lenses/groups)	26/18
Special lenses	2 x Fluorite, 1 x Super UD, 1 x UD
Number of aperture blades	9
Smallest aperture	64
Close focusing distance (approx. m)	2.6
Largest magnification (x)	0.34
Steering ring	Via focus ring
Optical Image Stabilizer (OIS) ¹	4
Image stabilization IBIS x OIS ²	4.5
AF motor	Ring-USM
Remuneration	ASC, Super Spectra
fluorine	front

Accesories

lens cap	E-180E
Lens hood	ET-155 (W III)
Lens case/bag	Lens case LS600
Lens rear cap	RF lens rear cap
compatibility with extender	Yes, compatible with RF extenders
Other accessories	Canon 52mm drop-in filters, Canon 52mm circular polarizing drop-in filter (W III), Canon short lens hood ET-155B

Specifications with 1.4x extender

Focal length	1120mm
Maximum aperture	8-9l
Maximum magnification	0.49 times
AF possible	Yes
Image stabilizer	Yes

Specifications with 2x extender

Focal length	1600mm
Maximum aperture	11-9l
Maximum magnification	0.71 times
AF possible	Yes
Image stabilizer	Yes

General Information

Dust/splash water protection	Yes, ³
Exterior coating	Heat-resistant
Filter diameter (approx. mm)	52
Diameter x Length (approx. mm) ⁴	163 x 432
Weight (approx. g)	3,140