

## Specifications

CCT	2,500K – 10,000K
CRI	>96
TLCI	>96
CQS (Tungsten)	95
CQS (Daylight)	96
SSI (Tungsten)	87
SSI (D56)	88
TM-30 RF (Average)	96
TM-30 RG (Average)	101
Operating Voltage Standard Output	100~240V 50/60Hz
Operating Voltage Full Output	180~240V 50/60Hz
Max Power Consumption (180-240V) Standard Mode	5600W
Max Power Consumption (180-240V) Extended Head Cable Mode	6000W
Max Power Consumption (100-179V)	3200W
Max Lamp Head Power Consumption (180V-240V)	5200W
Max LED Power Output (180V-240V)	4800W
AC Power Max Current	32A
Weather Resistance Rating	IP65
Native Beam Angle (No Reflector)	93°
Compatible Aputure Mount Reflectors	20°, 25°, 50° XT52 Reflectors
Max Head Cable Daisy Chain Length	45m
Operating Temperature	-20°C ~ 50°C / -4°F ~ 113°F
Storage Temperature	-40°C ~ 80°C / -40°F ~ 176°F
Cooling Method	Liquid + Air Cooling
Fan Noise Levels (1M) High Speed Mode	56.0dBA
Fan Noise Levels (1M) Default Mode	45.4dBA

## Control Methods

Control Methods	Onboard, Sidus Bluetooth, DMX, CRMX, Art-Net/sACN, Sidus Link Pro Auto-Patching and Auto-Configuration
Firmware Upgradeable	USB-A, Sidus Link, Sidus Link Pro
Wireless Range (Bluetooth & CRMX)	100m
Screen Type	TFT

## Dimensions

Lamp Head With Yoke	55.0 x 54.1 x 83.0cm 21.7 x 21.3 x 32.7in
Lamp Head Without Yoke	55.0 x 35.3 x 36.2cm 21.7 x 13.9 x 14.3in
Removable Yoke for STORM XT52	54.1 x 69.0cm 21.3 x 27.2in
Control Box	41.1 x 16.0 x 38.8cm 16.2 x 6.3 x 15.3in
Aputure Mount 35° Reflector	ø33.0 x 30.7cm ø16.2 x 6.3 x 15.3in

## Weight

Lamp Head With Yoke	31.30kg / 68.56lbs
Lamp Head Without Yoke	27.80kg / 61.29lbs
Removable Yoke for STORM XT52	3.50kg / 7.72lbs
Control Box	13.40kg / 29.54lbs
Aputure Mount 35° Reflector	1.50kg / 3.31lbs