

SA/CSA

Technical Data

Model	600SA	600CSA	900SA	900CSA	1200SA	1200CSA
LED Total Power	36W		54W		72W	
Input Voltage/Current	14.8V DC; 100-240V AC, Sony V-lock battery		14.8V DC; 100-240V AC, Sony V-lock battery		14.8V DC; 100-240V AC, Sony V-lock battery	
CRI	95		95		95	
TLCI	93		93		93	
CCT	5600K	3200K - 5600K	5600K	3200K - 5600K	5600K	3200K - 5600K
Dimming	0 to 100 % continuous		0 to 100 % continuous		0 to 100 % continuous	
Control	On-board controller, 2.4G		On-board controller, 2.4G		On-board controller, 2.4G	
Product Size	340 x 370 x 80mm 13.3 x 14.5 x 3.1"	345 x 385 x 90mm 13.5 x 15.1 x 3.5"	415x375x80mm 16.3x14.7x3.1"	420x375x90mm 16.5x14.7x3.5"	475x400x80mm 18.6x15.7x3.1"	470x380x90mm 18.4x14.9x3.5"
Weight	1.8kg / 4.0lb	2.1kg / 4.6lb	2.1kg / 4.6lb	2.4kg / 5.3lb	2.5kg / 5.5lb	2.5kg / 5.7lb
Certifications	CE, ROHS, KUCAS					

Illumination (lux/ftc)

Model	600SA	600CSA		900SA	900CSA		1200SA	1200CSA	
Distance	5600K	3200K	5600K	5600K	3200K	5600K	5600K	3200K	5600K
1m	5130lux 477fc	2280lux 212fc	2526lux 235fc	7700lux 716fc	3356lux 312fc	3464lux 322fc	9100lux 846fc	4900lux 455fc	5060lux 470fc
2m	1350lux 125.5fc	595lux 55fc	670lux 62fc	2040lux 190fc	860lux 80fc	897lux 83fc	2400lux 223fc	1284lux 119fc	1376lux 128fc
3m	620lux 58fc	281lux 26fc	311lux 29fc	930lux 86fc	396lux 37fc	415lux 38.5fc	1060lux 98.5fc	591lux 55fc	625lux 57fc
4m	350lux 32.5fc	162lux 15fc	181lux 17fc	540lux 50fc	233lux 22fc	246lux 23fc	612lux 67fc	340lux 32fc	364lux 34fc
5m	230lux 21fc	107lux 10fc	119lux 11fc	350lux 32.5fc	156lux 15fc	169lux 16fc	400lux 37fc	229lux 21fc	243lux 23fc