

Model	<i>Forza 60C</i>
Rated Power	88W
Input Voltage/Current	DC 15V/6A Max, AC 100-240V 50/60Hz
CCT	1800K-20000K (G/M±100)
CRI	Average 96
TLCI	Average 95
TM-30 Rf	Average 94
TM-30 Rg	Average 100
Dimming	0-100% continuous
Control	On-board, 2.4G, Bluetooth, NANLINK APP, DMX/RDM
Special Effects	HUE Loop, CCT Loop, INT Loop, Flash, Pulse, Storm, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding
Product Size	Light Fixture (Without COB Protective Cap): 224 × 110 × 88mm / 8.82 x 4.33 x 3.46" Power Adapter (With Holder Base): 141 × 82 × 50mm / 5.55 x 3.23 x 1.97"
Product Weight	Light Fixture: 1.08kg / 2.38lb Power Adapter: 0.47kg / 1.04lb (With Holder Base) Power Cable 3M: 0.12kg / 0.26lb Reflector: 0.08kg / 0.18lb
Master Carton Size	790 × 410 × 270mm / 31.10 × 16.14 × 10.63"
Packing Quantity	4
Certifications	CE, UKCA, FCC-ID, NCC, KC

Illumination (lux / fc)

Model	<i>Forza 60C</i>		
Light Only			
Distance	1M	2M	3M
2700K	5656 lux / 525 fc	1402 lux / 130 fc	631 lux / 59 fc
3200K	5694 lux / 529 fc	1433 lux / 133 fc	648 lux / 60 fc
4300K	5861 lux / 544 fc	1462 lux / 136 fc	658 lux / 61 fc

5600K	5709 lux / 530 fc	1425 lux / 132 fc	646 lux / 60 fc
7500K	5567 lux / 517 fc	1388 lux / 129 fc	630 lux / 59 fc
R	1282 lux / 119 fc	317 lux / 29 fc	142 lux / 13 fc
G	3855 lux / 358 fc	953 lux / 89 fc	428 lux / 40 fc
B	520 lux / 48 fc	129 lux / 12 fc	59 lux / 5 fc

With Reflector

Distance	1M	2M	3M
2700K	12470 lux / 1158 fc	2839 lux / 264 fc	1238 lux / 115 fc
3200K	12750 lux / 1184 fc	2939 lux / 273 fc	1278 lux / 119 fc
4300K	12970 lux / 1205 fc	2958 lux / 275 fc	1301 lux / 121 fc
5600K	12810 lux / 1190 fc	2946 lux / 274 fc	1283 lux / 119 fc
7500K	12460 lux / 1158 fc	2866 lux / 266 fc	1254 lux / 116 fc
R	2866 lux / 268 fc	656 lux / 61 fc	290 lux / 27 fc
G	8792 lux / 817 fc	2016 lux / 187 fc	876 lux / 81 fc
B	1200 lux / 111 fc	275 lux / 26 fc	120 lux / 11 fc

With FL-11 spot 10°

Distance	1M	2M	3M
2700K	35260 lux / 3276 fc	8303 lux / 771 fc	3539 lux / 329 fc
3200K	36350 lux / 3377 fc	8506 lux / 790 fc	3660 lux / 340 fc
4300K	37290 lux / 3464 fc	8761 lux / 814 fc	3794 lux / 352 fc
5600K	37520 lux / 3486 fc	8780 lux / 816 fc	3804 lux / 353 fc
7500K	36560 lux / 3396 fc	8530 lux / 792 fc	3712 lux / 345 fc
R	9440 lux / 877 fc	2171 lux / 202 fc	935 lux / 87 fc
G	24750 lux / 2299 fc	5753 lux / 534 fc	2503 lux / 233 fc
B	4940 lux / 459 fc	790 lux / 73 fc	340 lux / 32 fc

With FL-11 spot 45°

Distance	1M	2M	3M
2700K	10800 lux / 1003 fc	2720 lux / 253 fc	1222 lux / 114 fc
3200K	11000 lux / 1022 fc	2777 lux / 258 fc	1248 lux / 116 fc

4300K	11530 lux / 1071 fc	2903 lux / 270 fc	1302 lux / 121 fc
5600K	11310 lux / 1051 fc	2858 lux / 266 fc	1279 lux / 119 fc
7500K	11040 lux / 1026 fc	2792 lux / 259 fc	1250 lux / 116 fc
R	2594 lux / 241 fc	656 lux / 61 fc	293 lux / 27 fc
G	7480 lux / 695 fc	1879 lux / 175 fc	838 lux / 78 fc
B	1020 lux / 95 fc	256 lux / 24 fc	115 lux / 11 fc

With PJ-FMM-19

Distance	1M	2M	3M
2700K	40690 lux / 3780 fc	7673 lux / 713 fc	3164 lux / 294 fc
3200K	41920 lux / 3894 fc	7899 lux / 734 fc	3259 lux / 303 fc
4300K	43550 lux / 4046 fc	8140 lux / 756 fc	3331 lux / 309 fc
5600K	42700 lux / 3967 fc	8045 lux / 747 fc	3313 lux / 308 fc
7500K	41500 lux / 3855 fc	7825 lux / 727 fc	3231 lux / 300 fc
R	9950 lux / 924 fc	1870 lux / 174 fc	767 lux / 71 fc
G	28310 lux / 2630 fc	5272 lux / 490 fc	2144 lux / 199 fc
B	5330 lux / 495 fc	680 lux / 63 fc	280 lux / 26 fc

With PJ-FMM-36

Distance	1M	2M	3M
2700K	16130 lux / 1498 fc	3135 lux / 291 fc	1300 lux / 121 fc
3200K	16610 lux / 1543 fc	3269 lux / 304 fc	1358 lux / 126 fc
4300K	18090 lux / 1681 fc	3544 lux / 329 fc	1457 lux / 135 fc
5600K	17500 lux / 1626 fc	3468 lux / 322 fc	1440 lux / 134 fc
7500K	17140 lux / 1592 fc	3379 lux / 314 fc	1400 lux / 130 fc
R	4160 lux / 386 fc	812 lux / 75 fc	338 lux / 31 fc
G	11800 lux / 1096 fc	2284 lux / 212 fc	943 lux / 88 fc
B	1540 lux / 143fc	310 lux / 29 fc	126 lux / 12 fc