

MixPanel 60/150 *Technical Data*

Model	MixPanel 60	MixPanel 150
Rated Power	64W	164W
Input Voltage/Current	DC15V/6A Max, AC100-240V 50/60Hz	DC24V/7.5A Max, AC100-240V 50/60Hz
CRI	Average 95	Average 95
TLCI	Average 95	Average 95
CCT	2700K-7500K (G/M)	2700K-7500K (G/M)
Dimming	0-100%	0-100%
Control	On-board controller, 2.4G, DMX	On-board controller, 2.4G, DMX
Special Liting Effects	Hue Loop, CCT Loop, Flash, Pulse, Storm, Police car, TV, Paparazzi, Candle / Fire, Disco	
Product Size	426 × 370 × 82 mm / 16.77×14.57×3.23"	482 × 435 × 82 mm / 18.98×17.13×3.23"
Product Weight	Light	3.3 kg / 7.28 lb
	Light+Adapter	3.83 kg / 8.53 lb
		4.1 kg / 9.04 lb
		4.82 kg / 10.63 lb

Illumination (Lux/ft)

MixPanel 60

Distance	1M	2M	3M	4M	5M
2700K	4756 lux / 442 fc	1290 lux / 120 fc	596 lux / 55 fc	345 lux / 32 fc	228 lux / 21 fc
3200K	5438 lux / 505 fc	1485 lux / 138 fc	690 lux / 64 fc	395 lux / 37 fc	261 lux / 24 fc
5600K	5844 lux / 543 fc	1574 lux / 146 fc	729 lux / 68 fc	422 lux / 39 fc	279 lux / 26 fc
7500K	5695 lux / 529 fc	1534 lux / 143 fc	707 lux / 66 fc	410 lux / 38 fc	271 lux / 25 fc
R	1600 lux / 149 fc	429 lux / 40 fc	198 lux / 18 fc	116 lux / 11 fc	77 lux / 7 fc
G	3613 lux / 336 fc	958 lux / 89 fc	444 lux / 41 fc	259 lux / 24 fc	174 lux / 16 fc
B	690 lux / 64 fc	185 lux / 17 fc	85 lux / 8 fc	50 lux / 5 fc	33 lux / 3 fc

MixPanel 150

Distance	1M	2M	3M	4M	5M
2700K	10360 lux / 966 fc	2869 lux / 268 fc	1327 lux / 124 fc	768 lux / 72 fc	507 lux / 47 fc
3200K	12330 lux / 1150 fc	3401 lux / 317 fc	1557 lux / 145 fc	904 lux / 84 fc	600 lux / 56 fc
5600K	13880 lux / 1294 fc	3731 lux / 348 fc	1746 lux / 163 fc	1007 lux / 94 fc	663 lux / 62 fc
7500K	13280 lux / 1238 fc	3604 lux / 336 fc	1641 lux / 153 fc	957 lux / 89 fc	633 lux / 59 fc
R	2841 lux / 265 fc	758 lux / 71 fc	347 lux / 32 fc	203 lux / 19 fc	135 lux / 13 fc
G	6111 lux / 570 fc	1640 lux / 153 fc	758 lux / 71 fc	444 lux / 41 fc	296 lux / 28 fc
B	1240 lux / 116 fc	330 lux / 31 fc	152 lux / 14 fc	89 lux / 8 fc	60 lux / 6 fc