



S-mic 2S Condenser Microphone





Key Features

- Ultra Low Off-Axis Coloration
- Low Inherent Self-Noise
- Water Resistant and Humidity Proof
- RF-Interference Proof
- 24V or 48V phantom powering
- Super Cardioid Pickup Pattern

Product Description

- The Deity S-Mic 2S is a professional shotgun microphone offering superior sound performance, quality circuitry and great craftsmanship making for a reliable tool for audio recording.
- The Deity S-Mic 2S features a super cardioid pickup pattern which minimizes surrounding ambient sounds but still offers low off-axis coloration.
- The S-Mic 2S also is very forgiving when trying to point it at an actor or actress because of its super cardioid pickup, making it a great microphone for new boom operators.
- The microphone's ultra low self-noise lets you capture natural-sounding speech and dialog without any distractions.
- Designed to hold up to the brutality of run-and-gun-style shoots, the Deity S-Mic 2's body is machined from 100% solid brass and features a epoxy sealed gold-coated PCB board and a moisture-resistant capsule.
- All Deity S-Mic 2S come with a waterproof, shockproof hard case to keep your microphone safe during storage or travel. Also included with every purchase is a mic clip and a foam windscreen.
- The kit also features the Deity Microphones faux fur wind jammer that can be added over the foam

What's in the box

Pic	Name	Quantity
	S-mic 2S	1
	Microphone Clamp	1
	Windscreen	1
	Safe Case	1
	Desiccant	1
	Warranty Card	1
	Product Manual	1

Parameters

Polar Pattern	Super Cardioid
Maximum SPL	130dB SPL(@1KHZ,1% THD into 1K)
Frequency Rang	50~20kHz
THD	≤ 0.5%
Nominal Impedance	75Ω
Min. Terminating Impedance	Approx. 800
Sensitivity	-32±2dB re 1V/Pa @1kHz
Signal / Noise	79dB SPL (A-weighted per IEC651)
Input Voltage	24V or 48V phantom powering
Current Consumption	1.5mA
Temperature Range	-10°C to +70°C
Output	3-Pin XLR
Weight	89g
Dimensions	Φ19 x 148mm

More Pic

