

## 5. Specifications

Model Specification	HR672W	HR672S	HR672C
Operation Current	≤4A	≤4A	≤4A
Power	45W	45W	45W
Beam Angle	75°	25°	75°
Color Temperature	5500K	5500K	3200-5500K
Power Supply	DC 15V		
Average Life Span	≥100,000h		
Cooling Mode	Natural Ventilation		
Remote Frequency	2.4GHz		
Channels	3		
Groups	A/B/C/D		
Remote Range	≤100m		
Volume (L*W*H)	238*190*32mm		
Net Weight	585g		

## Brightness

Model	Distance	Footcandles	LUX
HR672W	0.5M	676	7300
	1M	193	2080
HR672S	0.5M	1741	18800
	1M	559	6040
HR672C	0.5M	613	6620
	1M	178	1920

## 6. Important Notice

- 1) Please do not directly face the LED when the lights are on.
- 2) Never block the ventilation grill by covering it with paper or clothes.
- 3) Do not place the LED light near alcohol or other flammable objects.
- 4) Keep all liquids away from LED panel.
- 5) When the LED light is on or against the other items above, please turn it off, lest they cause fire or damage to the light.
- 6) Do not make LED light face down when move the light stand.
- 7) Use a clean, dry, soft cloth to clean Amaran. Use only neutral detergents to remove the dirt and stains. Do not use strong cleaning agents such as thinner, gasoline, or alcohol.

The instruction and information in this manual are based on strict, controlled company testing procedures. Further notice will not be given if the design and specifications change. Sony is a trademark or registered trademark of Sony Corporation in the P.R.C. and other countries.