

# amaran

## COB 60d Feature Sheet



### Main Features

- **65W Output Daylight Bowens Mount Point-Source LED**
- **45,100lux @ 1 meter**
- **Full Size Bowens Mount**, the most universal accessory mount in a compact design
- **Bowens Mount Hyper Reflector (Mini)**: Specially Designed with a 15° Beam Angle
- **5600K Daylight CCT**
- **Super Accurate Color Rendition**, CRI:  $\geq 96$ , TLCI:  $\geq 96$ , SSI (D56): **72**
- **Compact & Lightweight**: Just Over 11x11x11cm and 675g
- **Stepless Dimming from 0 to 100%**
- **Sidus Link App Compatible**
- **Included Dual Sony NP-F Battery Plate**
- **D-Tap Battery Compatible** [D-Tap Power Cable (DC 5.5mm) Sold Separately\*]
- **Locking 19V DC 5.5mm Input**
- **8 Lighting FX**: Paparazzi, Fireworks, Lightning, Faulty Bulb, TV, Pulse, Strobe, Explosion
- **Ultra-quiet Active Cooling System**
- Click Control Knob to **Toggle Through Intensity Presets**
- **LCD display**
- **1/4-20" Mounting Point**

**What's in the Box**  
Tilting Stand Mount with Umbrella Holder  
Operating Temperature Range:  $-10^{\circ}\text{C} \sim 40^{\circ}\text{C}$

| Product Name                                  | Quantity |
|---|----------|
| amaran COB 60d                                | 1        |
| Bowens Mount Hyper Reflector (Mini)           | 1        |
| Dual NP-F Battery Plate for DC Barrel (5.5mm) | 1        |
| Bowens Mount Protection Cover                 | 1        |
| 1/4-20in Mounting Pin with Stand Adapter      | 1        |
| AC Power Supply                               | 1        |
| IEC C13 AC Power Cable (4m)                   | 1        |
| amaran COB 60d Carrying Case                  | 1        |

### Photometrics

| CCT   | Source                 | .5M                   | 1M                  | 3M               | 5M               |
|-------|------------------------|-----------------------|---------------------|------------------|------------------|
| 5600K | No Reflector           | 13,360lux / 1,241fc   | 3,310lux / 307fc    | 379lux / 35fc    | 145lux / 13fc    |
|       | Hyper Reflector (Mini) | 149,200lux / 13,860fc | 45,100lux / 4,190fc | 4,720lux / 438fc | 1,664lux / 155fc |

### Product Description

The amaran COB 60d is an ultra-compact daylight LED video light with surprising output and full Bowens Mount versatility.

One of the latest point source LED video lights from the amaran COB series, the amaran COB 60d features a 65W daylight output. The 60d is as compact as a camera, weighing in at a featherweight 675 grams (1.49 pounds), with dimensions just over 11x11x11cm (4x4x4 inches).

The COB 60d's small stature contains a powerhouse LED., reaching up to 45,100lux at 1 meter, with the specially designed 15° Hyper Reflector (Mini), all while maintaining pristine color quality with CRI and TLCI scores of 96+.

Equipped with a full-size Bowens Mount, the amaran COB 60d is compatible with the largest selection of modifiers on the market, including the Aputure Light Dome SE, Light Dome Mini II, and Aputure Lantern, making it an incredibly versatile multi-tool.

Its compact body houses an intuitive LCD screen and control knob interface that seamlessly blends into the body of the fixture. The control knob can adjust the light in 1% increments and can be clicked to toggle through intensity presets quickly.

Using its integrated Sidus Mesh® technology, the COB 60d can also be controlled by the Sidus Link® App, granting it access to 8 lighting effects, including Paparazzi, Fireworks, Lightning, Faulty Bulb, TV, Pulse, Strobe, and Explosion. The user-friendly Sidus Link® App allows users to adjust their settings without ever leaving their camera.

The amaran COB 60d is also the perfect light for creating on the move. In addition to the included AC Power supply, creators can power it using the Dual Sony NP-F Battery Plate or a D-Tap Battery (cable sold separately), which can easily be attached to the V-Mount Quick Release, located on the side of the unit for easy operation.

Packaged in an EPP (expanded polypropylene) eco-friendly carrying case, which follows suit with the COB 60d's lightweight design, the included case protects the amaran fixture from whatever nature may

### Target Audience

With its compact and lightweight body design, convenient operation, and EPP carrying case, the amaran COB 60d is perfect for creators and filmmakers who need to pack light without sacrificing good lighting.

The variety of power solutions the amaran COB 60 series has access to makes it suitable for shooting anywhere, as long as you have NP-F or D-Tap batteries.

Its full-size Bowens Mount and concentrated reflector make it a fantastic multi-tool for soft or intense lighting. Its ultra-quiet active cooling system will also never interfere with any audio recordings for the most crucial moments, whether you're creating content at home or on the move.

The compact versatility of the amaran COB 60d makes it a pivotal addition to any content creator, videographer, or indie filmmaker's lighting arsenal.

## Technical Specifications

|                                    |                                    |                          |
|------------------------------------|------------------------------------|--------------------------|
| CCT                                | 5600K                              |                          |
| CRI                                | ≥96                                |                          |
| TLCI                               | ≥96                                |                          |
| CQS                                | ≥94                                |                          |
| TM-30 RF (Avg.)                    | 93                                 |                          |
| TM-30 RG (Avg.)                    | 101                                |                          |
| SSI (D56)                          | 72                                 |                          |
| Beam Angle<br>(Half-Peak<br>Angle) | No Reflector                       | 120°                     |
|                                    | Hyper Reflector<br>(Mini)          | 15°                      |
| Max Power Output                   | 65W                                |                          |
| Max Power Consumption              | 76W                                |                          |
| Operating Current                  | 4A                                 |                          |
| Operating<br>Voltage               | AC Power Input                     | 100V~240V, 50/60Hz       |
|                                    | AC Power Supply<br>Output          | 19V                      |
|                                    | D-Tap Battery                      | 12~16.8V                 |
|                                    | NP-F Battery                       | 12~16.8V (Two Batteries) |
| DC Input Connector                 | 2.1mm / 5.5mm Locking<br>DC Barrel |                          |
| AC Power Supply Output             | 3m DC (5.5mm) Cable<br>with Lock   |                          |
| AC Power Cable                     | IEC C13 AC Power Cable<br>(4m)     |                          |
| Operating Temperature              | -10°C ~ 40°C /<br>14°F~104°F       |                          |
| Control Methods                    | On-board, Sidus Link App           |                          |
| Connectivity                       | Bluetooth 5.0 (Sidus<br>Mesh)      |                          |
| Bluetooth Operating Range          | ≥80m / 262.5ft                     |                          |
| Firmware Upgradeable               | Sidus Link OTA                     |                          |
| Display Type                       | LCD                                |                          |
| Cooling Method                     | Active Cooling                     |                          |
| Mounting                           | 1/4-20" Mounting Point             |                          |



# amaran

## COB 60d Feature Sheet

|            |                  |  |
|------------|------------------|--|
| Dimensions | Fixture          | 11.7* 11.1 *11.1cm /<br>4.60*4.37*4.37in |
|            | Aperture         | COB φ2cm / 0.79in                        |
|            | Carrying Case    | 32.7*27*14.8cm/<br>12.87*10.62*5.82in    |
|            | Power Supply     | 13.5*5.8*3.5cm /<br>5.31*2.28*1.38in     |
|            | Mounting Support | 14*5.5*5.5cm /<br>5.51*2.17*2.17in       |
| Weight     | Fixture          | 675g / 1.49lbs                           |
|            | Power Supply     | 557g / 1.23lbs                           |
|            | Mounting Bracket | 255g / 0.56lbs                           |
|            | Total            | 2.060kg / 4.54lbs                        |

## Sales and Shipping Information

|                    |   |               |
|--------------------|---|---------------|
| Product Name       | amaran COB 60d                            |               |
| SKU                | EU Plug                                   | APA0209A12    |
|                    | UK Plug                                   | APA0209A13    |
| UPC                | EU Plug                                   | 6971842182251 |
|                    | UK Plug                                   | 6971842182268 |
| Packing Dimensions | 32.7*27.0*14.8 cm /<br>12.87*10.62*5.82in |               |
| Net Weight         | 2.06kg / 4.54lbs                          |               |
| Gross Weight       | 2.50kg / 5.51lbs                          |               |
| Carton Qty         | 2pcs / Carton                             |               |
| Carton Dimensions  | 34.5*31.5*29.0 cm /13.58*12.4*11.42<br>in |               |
| Carton Weight      | 5.75kg / 12.68lbs                         |               |